



Gummifederelement **VIB** Typ: **AR-T** / Elastic Components **VIB** Type: **AR-T**



Typ Type	Code-Nr. Code no.	A	B ^{+0,25} _{+0,00}	D ^{+0,10} _{-0,20}	E	L	L1 ^{+0,0} _{-0,3}	Drehmoment Q in Nm bei $\neq \beta$ Torque Q in Nm at $\neq \beta$						Gewicht Weight in kg
								5°	10°	15°	20°	25°	30°	
AR-T 10 x 20	RE020010	11	8	20	2,5	20	25	0,3	0,8	1,3	1,9	2,8	3,8	0,05
AR-T 10 x 30	RE020011	11	8	20	2,5	30	35	0,4	1,2	2,0	2,9	4,2	5,7	0,06
AR-T 10 x 50	RE020012	11	8	20	2,5	50	55	0,7	2,0	3,3	4,8	7,0	9,5	0,09
AR-T 20 x 25	RE020015	15	11	27	2,5	25	30	0,7	1,6	2,5	3,8	5,4	7,8	0,08
AR-T 20 x 40	RE020016	15	11	27	2,5	40	45	1,1	2,5	4,0	6,1	8,7	12,5	0,14
AR-T 20 x 60	RE020017	15	11	27	2,5	60	65	1,6	3,8	6,0	9,2	13,0	18,8	0,20
AR-T 30 x 30	RE020020	18	12	32	2,5	30	35	1,8	4,2	7,0	10,5	14,3	19,5	0,14
AR-T 30 x 50	RE020021	18	12	32	2,5	50	55	3,0	7,0	11,7	17,5	23,8	32,5	0,22
AR-T 30 x 80	RE020022	18	12	32	2,5	80	85	4,8	11,2	18,9	28,0	38,2	52,0	0,35
AR-T 40 x 40	RE020025	27	22	45	2,5	40	45	4,7	10,2	16,5	25,6	37,6	54,2	0,28
AR-T 40 x 60	RE020026	27	22	45	2,5	60	65	6,8	15,3	24,8	38,4	56,4	81,3	0,42
AR-T 40 x 100	RE020027	27	22	45	2,5	100	105	11,8	25,5	41,2	64,0	94,0	135,5	0,68
AR-T 50 x 60	RE020030	38	30	60	5	60	70	12,4	29,0	48,2	74,0	107,5	153,5	0,69
AR-T 50 x 80	RE020031	38	30	60	5	80	90	16,5	38,7	64,3	98,7	143,4	204,7	0,94
AR-T 50 x 120	RE020032	38	30	60	5	120	130	24,7	58,0	96,4	148,0	215,0	307,0	1,35
AR-T 60 x 80	RE020035	45	35	72	5	80	90	26,4	60,0	98,6	152,4	210,5	302,0	1,19
AR-T 60 x 100	RE020036	45	35	72	5	100	110	33,0	75,0	123,2	190,5	263,1	377,5	1,48
AR-T 60 x 150	RE020037	45	35	72	5	150	160	49,5	112,5	184,8	285,8	394,6	566,3	2,19
AR-T 70 x 120	RE020040	50	40	78	5	120	130	50,0	121,0	225,0	356,0	513,0	741,0	2,15
AR-T 70 x 200	RE020041	50	40	78	5	200	210	100,0	237,0	428,0	670,0	963,0	1378,0	3,51
AR-T 70 x 300	RE020042	50	40	78	5	300	310	147,0	350,0	630,0	990,0	1431,0	2052,0	5,19



Typ **AR-T** mit Spanneisen **SR**
Type **AR-T** with **SR** clamp

MATERIALIEN

Der externe Körper und das interne Rohr von quadratischem Querschnitt sind aus Stahl.

BEHANDLUNG

Der externe Körper ist ofenlackiert, das interne Rohr ist elektrolytisch verzinkt.

FIXIERUNG

Die interne Verkopplung erfolgt mittels eines kaltgezogene Pulsts, der sich durch leicht abgerundete Ecken auszeichnet, oder durch Reibung mit einem passierenden Bolzen. Für die letztgenannte Lösung empfehlen wir den ausschließlichen Gebrauch von Größen **10-20-30**. Zum besseren Verständnis sind die Toleranzbereiche des internen Rohrs in der oben dargestellten Tabelle angegeben. Die Verankerung des externen Quaders kann mittels eines Spanneisens vom Typ **SR** erreicht werden, wie die nebenstehende Zeichnung verdeutlicht.

MATERIAL

The external body and the inner square section tube are made of steel.

TREATMENTS

The external body is oven-painted while the inner square is galvanized.

FITTING

Internal coupling is obtained with square-drawn section with slightly smoothed angles, or by friction using a passing screw but in this case we recommend to use only 10-20-30 sizes. The tolerances of the internal channel are listed in the above table. The external square structure can be fixed by the SR clamp as illustrated in the side drawing.