



MODULAR TRANSFER PLATES




Modular transfer plates with lip (width 115 mm 3 rows of rollers) - Part. D58 and DX58 Modulo di trasferimento con penna (larghezza 115 mm 3 file di rullini) - Part. D58 e DX58









Rollers made of stainless steel AISI 304 Rullini i<u>n acciaio inox AISI 304</u>

Rollers made of polyethylene Rullini in polietilene


With bearing/Con cuscinetti With bushing/Con boccole Type/Tipo Code/Codice Type/Tipo Code/Codice Type/Tipo Code/Codice DX58A CPA00464 DX58B CPA00474 D58 CP000474


MATERIALS: Modular transfer plate with external module made of grey colour acetal; rollers made of grey colour polyethylene or stainless steel AISI 304; bearings made of chrome steel; bushings made of auto-lubricating polyamide; pins and fixing nuts made of stainless steel AISI 304. FEATURES: To be assembled at the end of your conveyor to help the products transfer. Low friction coefficient, minimum noise level, extremely cleanable. The versions with rollers made in stainless steel, are available both with bearings made of chrome steel or with bushings made of auto-lubricating polyamide which are suitable for applications in contact with water.


MATERIALI: Modulo con corpo esterno in acetalica colore grigio; rullini in polietilene colore grigio o acciaio inox AISI 304; cuscinetti in acciaio al cromo; boccole in poliammide autolubrificante, perni e bulloni di fissaggio in acciaio inox AISI 304. CARATTERISTICHE: Da applicare alla fine del nastro trasportatore per il trasferimento del prodotto. Basso coefficiente di attrito, rumorosità contenuta, estremamente sanificabile. Le versioni con rullini in acciaio inox sono disponibili con cuscinetti in acciaio al cromo, oppure con boccole in poliammide autolubrificante per applicazioni a contatto con l'acqua.

Modular transfer plates with lip (width 115 mm 2 rows of rollers) - Part. D59 and DX59 Modulo di trasferimento con penna (larghezza 115 mm 2 file di rullini) - Part. D59 e DX59









Rollers made of stainless steel AISI 304

Rullini in acciaio inox AISI 304

Rollers made of polyethylene Rullini in polietilene

With bearing/Con cuscinetti		With bushing/Con boccole			
Type/ <i>Tipo</i>	Code/Codice	Type/ <i>Tipo</i>	Code/Codice	Type/Tipo	Code/Codice
DX59A	CPA00462	DX59B	CPA00475	D59	CP000475

MATERIALS: Modular transfer plate with external module made of grey colour acetal; rollers made of grey colour polyethylene or stainless steel AISI 304; bearings made of chrome steel; bushings made of auto-lubricating polyamide; pins and fixing nuts made of stainless steel AISI 304. FEATURES: To be assembled at the end of your conveyor to help the products transfer. Low friction coefficient, minimum noise level, extremely cleanable. The versions with rollers made in stainless steel, are available both with bearings made of chrome steel or with bushings made of auto-lubricating polyamide which are suitable for applications in contact with water.

MATERIALI: Modulo con corpo esterno in acetalica colore grigio; rullini in polietilene colore grigio o acciaio inox AISI 304; cuscinetti in acciaio al cromo; boccole in poliammide autolubrificante; perni e bulloni di fissaggio in acciaio inox AISI 304. CARATTERISTICHE: Da applicare alla fine del nastro trasportatore per il trasferimento del prodotto. Basso coefficiente di attrito, rumorosità contenuta, estremamente sanificabile. Le versioni con rullini in acciaio inox sono disponibili con cuscinetti in acciaio al cromo, oppure con boccole in poliammide autolubrificante per applicazioni a contatto con l'acqua



Suitable for applications which require maximum smoothness. Indicato per applicazioni che richiedono la massima scorrevolezza Suitable for applications in contact with water.

