




附件 型号 XVR / XVR accessories



 具高分子密度聚乙烯半圆形XVR滑块，适用于以经济的方式对速度不超过0.35m/s的单排、双排、三排链条进行张紧，工作温度低于 80°C。这个型号的滑块尤其适用于靠近链轮的安装和低轴距，或者存在足够的弧度半径。所供应配件包括所有的不锈钢螺钉螺栓。

 *XVR semi-circular sliding block in polyethylene with an high molecular density, suitable to tension in a cheaper way simplex, duplex or triplex chains which have a speed not higher than 0,35m/s and operating temperatures lower than 80°C.*

*This type of sliding block is particularly suitable for installations close to the pinion and for reduced interaxis, or when there is an adequate radius of curvature. The kits are delivered complete with stainless steel bolts and screws.*

型号 Type	S 编号 n°	D 编号 n°	T 编号 n°	链条 Chain	尺寸 Size 												重量 Weight [Kg]		
						A	B	C	D	E	F	G	H	L	M	S	D	T	
XVR 10-0	RE011975	RE011995		8mm	10	45	45		10	12		10	35	2.5	M 8	0.09	0.10		
XVR 10-1	RE011976	RE011996		3/8"x7/32"	10	45	45		10	18		10	35	5	M 8	0.09	0.10		
XVR 20-1			RE012015	3/8"x7/32"	20			45			25	10	35	5	M10			0.12	
XVR 20-2	RE011979	RE011999		1/2"x5/16"	20	55	55		14	20.5		10	35	7	M10	0.10	0.11		
XVR 30-2	RE011979	RE012000	RE012017	1/2"x5/16"	30	55	60	70	14	20.5	34	10	35	7	M10	0.11	0.12	0.13	
XVR 30-3	RE011981	RE012001		5/8"x3/8"	30	55	70		16.5	25		12	45	9	M10	0.12	0.14		
XVR 40-3			RE012019	5/8"x3/8"	40			100			42	12	45	9	M12			0.27	
XVR 30-4	RE011983	RE012003		3/4"x7/16"	30	60	70		17.5	30		12	45	11	M10	0.13	0.15		
XVR 40-4	RE011984	RE012004	RE012021	3/4"x7/16"	40	80	80	100	17.5	30	49	12	45	11	M12	0.20	0.22	0.28	
XVR 40-5	RE011986	RE012006	RE012023	1"x17.02mm	40	80	90	100	18	47	79.5	20	55	16	M12	0.22	0.31	0.44	

S: 具单滑块配件 / kit with simplex sliding block

D: 具双滑块配件 / kit with duplex sliding block

T: 具三滑块配件 / kit with triplex sliding block

