

附件 型号 XOV / XOV accessories




具高分子密度的聚乙烯椭圆形 XOV 滑块，适用于以经济的方式对速度不超过0.35m/s的单排和双排链条进行张紧，工作温度低于 80°C。

这个型号的滑块尤其适用于靠近链轮的安装和中低轴距。与传统 XVR 型滑块相比，其特殊的形状允许双面使用，保证加倍的使用寿命。所供应配件包括所有的不锈钢螺钉螺栓。

英国国旗 XOV elliptical sliding block in polyethylene with an high molecular density, suitable to tension in a cheaper way simplex, duplex or triplex chains which have a speed not higher than 0,35m/s and operating temperatures lower than 80°C.

This type of sliding block is particularly suitable for installations close to the pinion and for reduced interaxis and the particular shape allows to used it on both the sides, granting an useful life which is double with respect to the one of the traditional XVR type sliding block. The kits are delivered complete with stainless steel bolts and screws.

型号 Type	S 编号 n°	D 编号 n°	T 编号 n°	链条 Chain	Size 	A	B	C	D	L	M	N	O	重量 Weight [Kg]		
														S	D	T
XOV 10-1	RE013001	RE013021		3/8"x7/32"	10	45	45		10.2	5	M 8	40	75	0.09	0.10	
XOV 20-1			RE013040	3/8"x7/32"	20			55	10.2	7	M10	40	75			0.11
XOV 20-2	RE013004	RE013024		1/2"x5/16"	20	55	55		13.9	7	M10	50	96	0.10	0.11	
XOV 30-2	RE013004	RE013025	RE013042	1/2"x5/16"	30	55	60	75	13.9	9	M10	50	96	0.11	0.12	0.13
XOV 30-3	RE013006	RE013026		5/8"x3/8"	30	55	70		16.6	11	M10	65	126	0.12	0.14	
XOV 40-3			RE013044	5/8"x3/8"	40			90	16.6	11	M12	65	126			0.16
XOV 30-4	RE013008	RE013028		3/4"x7/16"	30	60	70		19.5	5	M10	74	148	0.13	0.15	
XOV 40-4	RE013009	RE013029	RE013046	3/4"x7/16"	40	80	80	100	19.5	7	M12	74	148	0.20	0.22	0.25

S: 具单滑块配件 / kit with simplex sliding block

D: 具双滑块配件 / kit with duplex sliding block

T: 具三滑块配件 / kit with triplex sliding block

