

附件 型号 XRO / XRO accessories




具高分子密度的聚乙烯 XRO 滑轮，在钢制衬套上转动，适用于以经济的方式对速度不超过0,55m/s的单排、双排和三排链条进行张紧，工作温度低于 80°C。

这个型号的滑块尤其适用于靠近链轮的安装和低轴距，或者有高缠绕角度必要时的安装。所供应配件包括所有的不锈钢螺钉螺栓。

**UK** XRO polyethylene wheel with an high molecular density that turns on a steel bush, suitable to tension in a cheaper way simplex, duplex or triplex chains which have a speed not higher than 0,55m/s and operating temperatures lower than 80°C.

This type of sliding block is particularly suitable for installations close to the pinion and for reduced interaxis, or in the cases it is necessary an high winding angle. The kits are delivered complete with stainless steel bolts and screws.

型号 Type	S 编号 n°	D 编号 n°	T 编号 n°	链条 Chain	Size 	A	B	C	D	E	F	ØH	L	M	重量 Weight [Kg]		
						S	D	T									
XRO 10-0	RE012095	RE012115		8mm	10	45	45		18	18		70	2.5	M 8	0.14	0.15	
XRO 10-1	RE012096	RE012116		3/8"x7/32"	10	45	50		18	18		70	5	M 8	0.14	0.15	
XRO 20-1			RE012135	3/8"x7/32"	20			60			36	70	5	M10			0.21
XRO 20-2	RE012099	RE012119		1/2"x5/16"	20	55	55		18	36		70	7	M10	0.15	0.20	
XRO 30-2	RE012099	RE012120	RE012137	1/2"x5/16"	30	55	60	70	18	36	36	70	7	M10	0.16	0.22	0.23
XRO 30-3	RE012101	RE012121		5/8"x3/8"	30	55	70		18	36		90	9	M10	0.19	0.29	
XRO 40-3			RE012139	5/8"x3/8"	40			100			49	90	9	M12			0.43
XRO 30-4	RE012103	RE012123		3/4"x7/16"	30	55	70		18	36		90	11	M10	0.19	0.29	
XRO 40-4	RE012104	RE012124	RE012141	3/4"x7/16"	40	80	80	100	18	36	49	90	11	M12	0.25	0.35	0.46
XRO 40-5	RE012106	RE012126	RE012143	1"x17.02mm	40	80	90	100	18	49	82	110	16	M12	0.32	0.56	0.70

S: 具单滑轮配件 / kit with simplex wheel

D: 具双滑轮配件 / kit with duplex wheel

T: 具三滑轮配件 / kit with triplex wheel

