


附件 型号 XZK / XZK accessories



链条拉紧装置用不锈钢链轮 XZK，具轴承，适用于对速度不超过 1m/s 的双排和三排链条进行张紧，工作温度低于 100°C。所供应配件包括不锈钢螺钉螺栓。

UK XZK stainless steel pinion tightener with bearing, suitable to tension simplex, duplex and triplex chains which have a speed not higher than 1m/s and operating temperatures lower than 100°C. The kits are delivered complete with Inox bolts and screws.

型号 Type	S 编号 n°	D 编号 n°	T 编号 n°	链条 Chain	Size 									重量 Weight [Kg]			
						A	B	C	D	ØH	L	ØP	M	Z	S	D	T
XZK 20-1	RE012310	RE012340		3/8"x7/32"	20	55	55		9	49.3	5.3	45.81	M10	15	0.13	0.23	
XZK 30-1	RE012310	RE012341	RE012370	3/8"x7/32"	30	55	60	70	9	49.3	5.3	45.81	M10	15	0.13	0.23	0.26
XZK 30-2	RE012314	RE012344		1/2"x5/16"	30	55	60		9	65.5	7.2	61.09	M10	15	0.21	0.37	
XZK 40-2			RE012374	1/2"x5/16"	40			80	12	65.5	7.2	61.09	M12	15			0.51
XZK 40-3	RE012318	RE012348	RE012377	5/8"x3/8"	40	80	80	80	12	83.0	9.1	76.36	M12	15	0.38	0.60	0.96
XZK 40-4	RE012321	RE012351	RE012381	3/4"x7/16"	40	80	80	90	12	99.8	11.1	91.63	M12	15	0.56	1.00	1.50
XZK 40-5	RE012325	RE012355		1"x17.02mm	40	100	120		12	117.0	16.2	106.12	M12	13	1.00	1.90	

Z: 齿数 / number of teeth

S: 具单链轮的配套元件 / kit with a simplex pinion

D: 具双链轮的配套元件 / kit with a duplex pinion

T: 具三链轮的配套元件 / kit with a triplex pinion

